



### TECHNICAL

These garments have been designed to give a specific level of protection against accidental contact with flame. They are not designed to withstand constant exposure to flame or molten metal splash.

The fabric conforms to EN533:1997 – Limited flame spread (ISO 14116)



### WARNING

The garment is FLAME RETARDANT not FLAME PROOF. The actual conditions of use cannot be simulated and it is the responsibility of the user, not the manufacturer, to determine the garments suitability for the intended use. The garment is sold without warranty expressed or implied. No warranty or representation is made to the products ability to protect the user from injury or death. The user assumes that responsibility.

### GARMENT CARE

Stored garments should be kept in a dry place away from heat or direct sunlight. New and used garments should be thoroughly inspected, especially after washing, to ensure no damage is present.

Hand or machine wash in water not exceeding 40 degrees centigrade using a good proprietary washing powder or detergent that does not contain optical whiteners or high levels of oxidising agents. Best results are given by using a liquid detergent with near neutral pH and water with minimum alkaline content. Do not use pure soap powders such as Fairy Snow, Lux, or Persil soap powder as these may affect the flame retardant properties of the garment. The machine cycle should not exceed 1 hour and do not exceed 2/3 of the machine capacity. Ensure that the rinse cycle is sufficient to remove all residual soap / detergents. Very important! Zip up all zippers and attach all Velcro before loading! Zipper sliders and teeth can easily be damaged in the washer or dryer. Velcro gets clogged up with fuzz from other garments and can snag your other clothes, causing damage to both. DO NOT USE BLEACH, PEROXIDE OR CAUSTIC WASHING AGENTS. Line dry, preferably not in direct sunlight, hang inside out to avoid fading of outer surface.

### WEARING AND FITTING

ALWAYS ENSURE YOUR ZIP FASTENER IS FULLY UNDONE WHEN GETTING IN OR OUT OF YOUR OVERALLS. WEARING OVERALL TIED AROUND WAIST BY THE SLEEVES WILL RESULT IN ZIP STRESS AND FAILURE. IF YOU HAVE NOT ALLOWED FOR WEARING SEVERAL LAYERS UNDER YOUR OVERALLS DURING COLD SPELLS THIS WILL RESULT IN EXCESSIVE STRAIN AND POSSIBLE FAILURE TO ZIP WHEN WORN.

### REPAIRS

Do not repair this garment using fabrics other than fabrics of similar construction and flame retardant properties. If in doubt, consult the manufacturer before repair.

